

SPECIFICATION SHEET

Prioma™ Medical Bed 600




**Affordable,
essential
everyday
care**

Standard Features

- Safe Working Load (SWL) 250 Kg
- Tente 125mm single central locking castors
- Linak actuators
- ABS removable deck panels
- Full length split side rails
- Embedded controls for nurse and patient
- Retracting backrest
- Manual CPR backrest quick release
- Foot/calf elevation - manually operated
- Foot end central lock pedals
- Urine bag hooks and strap rail - both sides of bed
- Four accessory sockets
- Soft contoured mattress retainer handles
- Removable lightweight head and foot panels
- Head and foot end rotating wall buffers
- Trendelenburg & reverse Trendelenburg tilt 14°

Model pictured with 3/4 length split side rails and twin central locking castors.



Optional Features

- Tente 125mm individual locking castors
- Tente 125mm twin central locking castors
- Tente 150mm single central locking castors
- Tente 150mm twin central locking castors
- Head end central lock foot pedals¹
- 3/4 length split side rails
- Battery back up unit
- ACOM cabled hook over attendant control panel
- HB70 Patient handset
- HB70 Nurse handset
- Under bed light (set in permanent on-mode)
- Integral bed extension - 285mm extension
- Integral linen rack - 300mm extension²
- Range of accessories

Basic Dimensions

Overall length	2195 mm
Overall length base extension extended	2480 mm
Linen rack extension	300 mm
Overall width	1010 mm
In bed dimensions - inside panel to inside panel, inside mattress retainer to mattress retainer	2030 mm (l) x 860 mm (w)
Deck height range - Tente 125mm single central locking castors	380 mm to 835 mm
Trendelenburg and reverse Trendelenburg tilt - electronic	0 to 14°
Backrest angle adjustment - electronic	0 to 70°
Knee break angle adjustment - electronic	0 to 35°

Product Weight (approximate)

Includes side rails fitted	148 Kg
Safe Working Load (SWL)	250 Kg
Maximum patient weight	185 Kg

Electrical Data

Power in - switch mode operating voltage range 100V to 240V - 50/60Hz

Duty rating - intermittent 10%, max 2 min / 18 min

Electric Shock Protection - Class 1 Type B

Liquid ingress protection - IP54

Internally powered equipment - battery backup only - 2 x 12V series connected batteries, sealed chargeable lead/Acid Gel 1.2 amp hours

¹ Feature only available if central locking castors are fitted.

² Only available with built in bed extension.

At Arjo, we are committed to improving the everyday lives of people affected by reduced mobility and age-related health challenges. With products and solutions that ensure ergonomic patient handling, personal hygiene, disinfection, diagnostics, and the effective prevention of pressure ulcers and venous thromboembolism, we help professionals across care environments to continually raise the standard of safe and dignified care. Everything we do, we do with people in mind. www.arjo.com

Arjo AB, Hans Michsensgatan 10, SE-211 20 Malmö, Sweden. Phone: +46 (0) 10 335 45 00

www.arjo.com